

Ivory colored plastic reinforced transparent PU hose, medium-sized wear-resistant

Product images	Application	Characteristic	Structure
	► Transportation of food grade granular materials	► Smooth inner wall	► Color: Transparent pipe wall
	► Transportation of food powder materials	► Soft and easy to bend in texture	Reinforced ivory/grey color
	► Transportation of edible oils and fats	► Good wear resistance	► Temperature: -30/+80°C
	► Delivery of beverages with an alcohol concentration of less than 20%	► Good liquidity	► Standard:
	► Pharmaceutical industry	► Good airtightness	Compliant with FDA Food Contact Safety Standards
► Hose wall: Polyether polyurethane	► Food factory	► Good chemical resistance	Compliant with the EU 10/2011 Food Contact Material Standard
► Reinforcement: PVC plastic reinforcement	► New Energy Lithium Battery Industry	► Good UV resistance	
► There is a regular industrial 921 available for purchase	 	► Ozone resistant, hydrolysis resistant, mold resistant	
► Anti static 921FE is available for purchase			

Part Number	Internal Diameter mm	Min Wall th mm	Max Wall th mm	Weight kg/m	Bending Radius mm	Vacuum bar	Coil Length m
921F-013-20	13	0.40	2.80	0.08	20	0.25	20
921F-016-20	16	0.40	2.80	0.10	25	0.25	20
921F-019-20	19.1	0.40	2.80	0.11	25	0.25	20
921F-020-20	20	0.40	2.80	0.12	25	0.25	20
921F-022-20	22	0.40	2.80	0.13	28	0.25	20
921F-025-20	25	0.40	2.80	0.15	30	0.25	20
921F-030-20	30	0.40	2.80	0.17	35	0.25	20
921F-032-20	31.8	0.40	2.90	0.19	35	0.20	20
921F-035-20	35	0.50	3.00	0.21	45	0.20	20
921F-038-20	38.1	0.50	3.10	0.24	50	0.20	20
921F-040-20	40	0.50	3.10	0.26	60	0.20	20
921F-045-20	45	0.50	3.20	0.30	65	0.20	20
921F-050-20	50	0.50	3.40	0.35	70	0.20	20
921F-052-20	50.8	0.50	3.40	0.35	70	0.20	20
921F-055-20	55	0.50	3.60	0.41	75	0.20	20
921F-060-20	60	0.50	3.80	0.49	80	0.16	20
921F-063-20	63.5	0.50	3.90	0.54	80	0.16	20
921F-065-20	65	0.50	3.90	0.55	90	0.16	20
921F-070-20	70	0.60	4.20	0.59	95	0.16	30
921F-076-30	76.2	0.60	4.20	0.64	100	0.16	30
921F-080-30	80	0.60	4.50	0.68	110	0.16	30
921F-090-30	90	0.60	4.60	0.79	125	0.14	30
921F-100-30	100	0.60	4.80	0.85	140	0.13	30
921F-102-30	102	0.60	4.80	0.87	140	0.13	30
921F-110-30	110	0.60	5.10	1.00	150	0.12	30
921F-120-30	120	0.60	5.40	1.19	160	0.10	30
921F-127-30	127	0.60	5.40	1.26	170	0.10	30
921F-127-20	130	0.70	5.70	1.44	170	0.09	20
921F-140-20	140	0.70	5.70	1.54	180	0.09	20
921F-150-20	151.5	0.70	5.80	1.60	200	0.08	20
921F-152-20	152.4	0.70	5.80	1.61	200	0.08	20
921F-160-20	160	0.70	7.20	2.05	220	0.07	20
921F-180-20	180	0.70	7.20	2.30	250	0.04	20
921F-200-20	200	0.70	7.20	2.37	260	0.04	20
921F-203-20	203.2	0.70	7.20	2.41	260	0.04	20
921F-250-10	250	0.80	8.00	3.57	300	0.04	10
921F-300-10	300	0.80	8.20	4.45	350	0.03	10

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating

**** * We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.

Zimflex(Shanghai) Industrial Hose Co., Ltd.

www.zimflex.com